

Safety data sheet

according to 1907/2006/EC, Article 31

Revision: 22.02.2018 Printing date 20.04.2018 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier • Trade name: xylene, mixture of isomers • Article number: 2425 · CAS Number: 1330-20-7 · EC number: 215-535-7 · Index number: 601-022-00-9 · Registration number 01-2119484621-37-XXXX · 1.2 Relevant identified uses of the substance or mixture and uses advised against Only for the use of professionals users · Life cycle stages IS Use at industrial Sites F Formulation or re-packing PW Widespread use by professional workers · Sector of Use *SU8 Manufacture of bulk, large scale chemicals (including petroleum products)* SU9 Manufacture of fine chemicals · Process category PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions **PROC3** Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition *PROC4* Chemical production where opportunity for exposure arises PROC5 Mixing or blending in batch processes **PROC7** Industrial spraving PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC10 Roller application or brushing PROC11 Non industrial spraying PROC13 Treatment of articles by dipping and pouring PROC14 Tabletting, compression, extrusion, pelletisation, granulation PROC15 Use as laboratory reagent PROC19 Manual activities involving hand contact PROC24 High (mechanical) energy work-up of substances bound in /on materials and/or articles · Environmental release category ERC1 Manufacture of the substance ERC2 Formulation into mixture ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC7 Use of functional fluid at industrial site ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) *ERC8c* Widespread use leading to inclusion into/onto article (indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) *ERC8f* Widespread use leading to inclusion into/onto article (outdoor) • Application of the substance / the mixture Chemical for research, development, manufacturing, laboratory chemical for analysis. (Contd. on page 2) EU

Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.04.2018	Revision: 22.02.20
Trade name: xylene, mixture of isomers	
	(Contd. of page
	(Conta. of page
• 1.3 Details of the supplier of the safety data sheet	
• <i>Manufacturer/Supplier:</i> Biosolve Chimie	
20 Rue Roger Husson, 57260 Dieuze, France	
<i>Tel:</i> +33 3 878 675 80/81/82/83/84/85	
Email: info@biosolvechimie.com	
Biosolve B.V.	
Leenderweg 78, 5555 CE Valkenswaard, the Netherlands. Tel: +31-(0)40-2071300	
<i>Fax:</i> +31-(0)40-2048537	
Email: info@biosolve-chemicals.com	
• Further information obtainable from: Product safety departm	ent
• 1.4 Emergency telephone number:	
For emergency telephone numbers of the poisons cente	rs in Europe please use this link: http:
www.eapcct.org/	
SECTION 2: Hazards identification	
 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 flame 	
Classification according to Regulation (EC) No 1272/2008	
Classification according to Regulation (EC) No 1272/2008	
Classification according to Regulation (EC) No 1272/2008	
Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07	
Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin.	
Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled.	
Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.	
Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. • 2.2 Label elements	
 Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 	regulation.
 Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The substance is classified and labelled according to the CLP 	regulation.
 Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 	regulation.
 Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The substance is classified and labelled according to the CLP 	regulation.
 Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The substance is classified and labelled according to the CLP 	regulation.
Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The substance is classified and labelled according to the CLP Hazard pictograms Contemportation (EC) No 1272/2008	regulation.
 Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The substance is classified and labelled according to the CLP 	regulation.
Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The substance is classified and labelled according to the CLP Hazard pictograms Contemportation (EC) No 1272/2008	regulation.
 Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The substance is classified and labelled according to the CLP Hazard pictograms GHS02 GHS07 Signal word Warning Hazard statements 	regulation.
Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The substance is classified and labelled according to the CLP Hazard pictograms GHS02 GHS07 Signal word Warning Hazard statements H226 Flammable liquid and vapour.	regulation.
Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The substance is classified and labelled according to the CLP Hazard pictograms GHS02 GHS07 Signal word Warning Hazard statements H226 Flammable liquid and vapour. H312+H332 Harmful in contact with skin or if inhaled.	regulation.
 Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The substance is classified and labelled according to the CLP Hazard pictograms GHS02 GHS07 Signal word Warning Hazard statements H226 Flammable liquid and vapour. 	regulation.







Revision: 22.02.2018

Trade name: xylene, mixture of isomers

· Precautionary statements

Printing date 20.04.2018

(Contd. of page 2)

1.0000000000000000000000000000000000000	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with
	water [or shower].
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
2 2 Other harands	-

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.1 Chemical characterisation: Substances
- · CAS No. Description
- 1330-20-7 xylene, mixture of isomers
- · Identification number(s)
- EC number: 215-535-7
- · Index number: 601-022-00-9

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31



 Printing date 20.04.2018
 Revision: 22.02.2018

 Trade name: xylene, mixture of isomers
 Revision: 22.02.2018

• 5.3 Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- \cdot 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling
- *Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.*
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene, mixture of isomers

IOELV Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin

• *Additional information:* The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

(Contd. on page 5)

(Contd. of page 3)

Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31



Revision: 22.02.2018

Trade name: xylene, mixture of isomers

(Contd. of page 4)

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

Printing date 20.04.2018

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

General Information Appearance:		
Form:	Fluid	
Colour:	Colourless	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition Melting point/freezing point: Initial boiling point and boiling re	-34 °C Inge: 137-143 °C	
Flash point:	30 °C	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	500 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Not determined.	



Printing date 20.04.2018

Revision: 22.02.2018

Trade name: xylene, mixture of isomers

	(Contd. of page 3
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
Vapour pressure at 20 °C:	6.7-8.2 hPa
Density at 20 °C:	$0.87 \ g/cm^3$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water at 20 °C:	0.2 g/l
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic at 20 °C:	0.61 mPas
Kinematic:	Not determined.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful in contact with skin or if inhaled.

· LD/LC50 values relevant for classification:

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

· Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)







Revision: 22.02.2018

Trade name: xylene, mixture of isomers

Printing date 20.04.2018

(Contd. of page 6)

- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- *STOT-single exposure Based on available data, the classification criteria are not met.*
- \cdot **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

- HP 3 Flammable
- HP 4 Irritant skin irritation and eye damage
- HP 6 Acute Toxicity

· Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.*

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1307	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	UN1307 XYLENES XYLENES	
		(Contd. on page 8)

ntd. on page 8)



Printing date 20.04.2018

Revision: 22.02.2018

	(Contd. of pa
14.3 Transport hazard class(es)	
ADR	
A	
▼	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDĞ, IATA	111
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	3-07
Stowage Category	A
14.7 Transport in bulk according to Ann	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
Transport category	Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	D/E
IMDG Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
(22)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1307 XYLENES, 3, III

(Contd. on page 9)



rade name: xyl	lene, mixture of isomers
	(Contd. of page 8)
SECTION	15: Regulatory information
• Labelling ac The substance	health and environmental regulations/legislation specific for the substance or mixture ecording to Regulation (EC) No 1272/2008 the is classified and labelled according to the CLP regulation.
• Hazard picto)grams
	\wedge
<u> く 砂 入く</u>	
	$\mathbf{\nabla}$
GHS02 C	GHS07
· Signal word	
• Hazard state	
H226	Flammable liquid and vapour.
	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
• Precautiona	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361-	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with
	water [or shower].
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Directive 20	12/18/FU
	gerous substances - ANNEX I Substance is not listed.
	gory P5c FLAMMABLE LIQUIDS
	<i>juantity (tonnes) for the application of lower-tier requirements 5,000 t</i>
	<i>juantity (tonnes) for the application of upper-tier requirements 50,000 t</i>
	ON (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
• 15.2 Chemic	cal safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

- · Contact: Product safety department
- Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LCS0: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)

Printing date 20.04.2018

Revision: 22.02.2018

⁻ EU



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.04.2018

Revision: 22.02.2018

Trade name: xylene, mixture of isomers

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 • * **Data compared to the previous version altered.** (Contd. of page 9)

EU