

Printing date 09/03/2013 Reviewed on 07/16/2013

1 Identification of the substance/mixture and of the company

- · Product identifier
- · Trade name: SU-8 3000 Series Resists
- · Product number: Y311075, Y311074, Y311072, Y311060, Y311049
- · Application of the substance / the preparation Photoresist
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MicroChem Corp.

90 Oak Street

P.O. Box 426

Newton, MA 02464-0002 USA

· Information department:

Product Safety

Email: productsafety@microchem.com

· Emergency telephone number: MicroChem Corp: 617-965-5511

Chemtrec USA Émergency: 800-424-9300

Chemtrec International Emergency: 703-527-3887

2 Hazards identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Muta. 2 H341 Suspected of causing genetic defects.



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

| Acute Tox. 4 | H302 | Harmful if swallowed. |
|---------------|-----------|----------------------------------------------------------------------|
| Acute Tox. 4 | H312 | Harmful in contact with skin. |
| Skin Irrit. 2 | H315 | Causes skin irritation. |
| Eye Irrit. 2A | H319 | Causes serious eye irritation. |
| Skin Sens. 1 | H317 | May cause an allergic skin reaction. |
| STOT SE 3 | Н335-Н336 | May cause respiratory irritation. May cause drowsiness or dizziness. |

- · Label elements
- GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS).

 (Contd. on page 2)

- USA

Printing date 09/03/2013 Reviewed on 07/16/2013

Trade name: SU-8 3000 Series Resists

(Contd. of page 1)

· Hazard pictograms









GHS02 GHS07

GHS08 GHS09

· **Signal word** Warning

· Hazard-determining components of labelling:

Cyclopentanone Epoxy resin

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Formaldehyde Polymer

Bis-triarylsulfonium hexafluoroantimonate salt Aromatic sulfonium hexafluoroantimonate salt

· Hazard statements

H226 Flammable liquid and vapor.

H302+H312 Harmful if swallowed or in contact with skin.

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P233 Keep container tightly closed.
 P273 Avoid release to the environment.
 P201 Obtain special instructions before use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.

P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

(Contd. on page 3)

Printing date 09/03/2013 Reviewed on 07/16/2013

Trade name: SU-8 3000 Series Resists

· HMIS-ratings (scale 0 - 4)

(Contd. of page 2)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

| Dangerous co | omponents: | |
|--------------|------------------------------------------------------------------------------------------------------------------------------------|----------|
| 28906-96-9 | Epoxy resin | 20-45% |
| | 🕸 Muta. 2, H341; ᡧ Eye Irrit. 2A, H319; Skin Sens. 1, H317 | |
| 120-92-3 | Cyclopentanone | 20-50% |
| | ♠ Flam. Liq. 3, H226; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335-H336 | - |
| 9003-36-5 | Formaldehyde Polymer | 10-25% |
| | ♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335 | |
| 244772-00-7 | Cycloaliphatic Epoxy Resin | 10-25% |
| | ♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319 | |
| 108-32-7 | Propylene carbonate | 1-5% |
| | ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319 | - |
| | Proprietary polyglycidyl ether | 1-5% |
| 89452-37-9 | Bis-triarylsulfonium hexafluoroantimonate salt | 1-5% |
| | ♦ Muta. 2, H341; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♦ Skin Sens. 1, H317 | |
| 71449-78-0 | Aromatic sulfonium hexafluoroantimonate salt | 1-5% |
| | ♦ Muta. 2, H341; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♦ Skin Sens. 1, H317 | |
| 2530-83-8 | [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | 0.5-2.0% |
| | Acute Tox. 3, H301; Acute Tox. 3, H331; & Muta. 2, H341; STOT RE 2, H373; b Eye Irrit. 2A, H319; STOT SE 3, H336 | |

4 First aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Immediately remove any clothing soiled by the product.

- · After inhalation: Supply fresh air and to be sure call for a doctor.
- · After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)



Printing date 09/03/2013 Reviewed on 07/16/2013

Trade name: SU-8 3000 Series Resists

(Contd. of page 3)

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Do not induce vomiting unless instructed to do so by a physician. Wash out mouth with water and keep person at rest. Seek immediate medical attention.

- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· For safety reasons unsuitable extinguishing agents:

Water with full jet

Water

· Special hazards arising from the substance or mixture

Containers may explode due to pressure increase when container is exposed to extreme heat. Vapors may travel a considerable distance to a source of ignition and flash back along vapor trail.

- · Advice for firefighters
- · Protective equipment: Wear SCBA.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any drains.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaust at the workplace.

Prevent formation of aerosols.

Keep receptacles tightly sealed.

(Contd. on page 5)



Printing date 09/03/2013 Reviewed on 07/16/2013

Trade name: SU-8 3000 Series Resists

(Contd. of page 4)

Keep away from heat and direct sunlight.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and containers:

Due to photo-sensitivity, store product in brown-glass or stainless steel receptacles.

· Information about storage in one common storage facility:

Do not store together with amines.

Do not store together with oxidizing and acidic materials.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Protect from exposure to the light.

Keep container well-sealed in cool, dry location.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

| | · Control parameters | | | | |
|---|--------------------------------------------------------------------------|--------------------------|--|--|--|
| | · Components with limit values that require monitoring at the workplace: | | | | |
| ſ | 89452-37-9 Bis-triarylsulfonium hexafluoroantimonate salt | | | | |
| Ī | ACGIH TLV TWA | 0.5 mg/m^3 | | | |
| | NIOSH IDLH | 50 mg/m^3 | | | |
| | OSHA PEL | 0.5 mg/m^3 | | | |
| Ī | 71449-78-0 Aromatic sulfonium hexafluoroantimonate salt | | | | |
| Ī | | ACGIH TLV TWA: 0.5 mg/m³ | | | |
| | NIOSH IDLH | 50 mg/m^3 | | | |
| | OSHA PEL | 0.5 mg/m^3 | | | |
| | | | | | |

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from food and beverages.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory equipment:

In case of low exposure, use cartridge respirator. In case of intensive or longer exposure, use SCBA.

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material Contact glove manufacture for break-through time.

(Contd. on page 6)




Printing date 09/03/2013 Reviewed on 07/16/2013

Trade name: SU-8 3000 Series Resists

· Eye protection:

(Contd. of page 5)



| Information on basic physical and | chemical properties |
|--------------------------------------|------------------------------------------------------------------------------------------|
| General Information Appearance: | |
| Form: | Liquid |
| Color: | Light yellow |
| Odor: | Recognizable |
| Odour threshold: | Not determined. |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 130 °C (266 °F) |
| Flash point: | 30 °C (86 °F) |
| Flammability (solid, gaseous): | Not applicable. |
| Ignition temperature: | 430 °C (806 °F) |
| Decomposition temperature: | Not determined. |
| Auto igniting: | Product is not selfigniting. |
| Danger of explosion: | Product is not explosive. However, formation of explosive air/vap mixtures are possible. |
| Explosion limits: | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| Vapor pressure: | Not determined. |
| Density: | Not determined. |
| Relative density | See Table 1 Other Information |
| Vapour density | Not determined. |
| Evaporation rate | Not determined. |
| Solubility in / Miscibility with | |
| Water: | Water miscible No |
| Partition coefficient (n-octanol/wat | (er): Not determined. |
| Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |



Printing date 09/03/2013 Reviewed on 07/16/2013

Trade name: SU-8 3000 Series Resists

(Contd. of page 6)

| · Solvent content: VOC content: | See Table 1 below | | | | | |
|------------------------------------|-------------------|---------|-----------|---------------|----------|--|
| · Other information | Name | Number | Sp. Grav. | Vol.(%by wt.) | VOC(g/L) | |
| _ | SU-8 3005 | Y311049 | 1.075 | 48-52 | 538 | |
| | SU-8 3010 | Y311060 | 1.106 | 38-42 | 442 | |
| | SU-8 3025 | Y311072 | 1.143 | 26-30 | 320 | |
| | SU-8 3035 | Y311074 | 1.150 | 24-28 | 300 | |
| | SU-8 3050 | Y311075 | 1.153 | 22-27 | 288 | |

10 Stability and reactivity

- · Reactivity
- · Chemical stability Stable under normal use conditions
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Exothermic polymerization.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials:

Strong Oxidizing Agents, Strong Bases, Strong Acids, Strong Reducing Agents, Iron, Hydrazine

· Hazardous decomposition products:

Carbon monoxide

Carbon dioxide

Danger of toxic pyrolysis products.

Corrosive gases/vapors

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

| <i>28906-96</i> | 9 Epoxy resin | | | |
|--------------------------------|--------------------------------------------------------------------------------------|-----------------------------|--|--|
| Oral | LD50 | >2000 mg/kg (rat) | | |
| Dermal | LD50 | >2000 mg/kg (rabbit) | | |
| Inhalative | LC50 | 5 mg/L (rat) | | |
| | 100 <lc 50<="" ec="" ic="" td=""><td>$\leq 1000 mg/l (algae)$</td></lc> | $\leq 1000 mg/l (algae)$ | | |
| | | $\leq 1000 \ mg/l \ (fish)$ | | |
| | | ≤1000 mg/l (invertebrates) | | |
| 2530-83-8 | 3 [3-(2,3-epoxypropo | oxy)propyl]trimethoxysilane | | |
| Oral | LD50 | 22600 mg/kg (rat) | | |
| Dermal | LD50 | 4250 mg/kg (rat) | | |
| Inhalative | LC50/4 h | > 5.3 mg/l (rat) | | |
| 120-92-3 | Cyclopentanone | | | |
| Oral | LD50 | 1180 mg/kg (rat) | | |
| Dermal | LD50 | >2000 mg/kg (rabbit) | | |
| Inhalative | LC50/4 h | >19.5 mg/l (rat) | | |
| 9003-36-5 Formaldehyde Polymer | | | | |
| 7000 00 0 | | | | |

— US/



Printing date 09/03/2013 Reviewed on 07/16/2013

Trade name: SU-8 3000 Series Resists

| 244772-00-7 Cycloaliphatic Epoxy Resin |
| Oral | LD50 | >2000 mg/kg (rat) |
| Proprietary polyglycidyl ether |
| Oral | LD50 | >2000 mg/kg (rat) |

· Specific symptoms in biological assay:

Epoxy resin CAS 28906-96-9:

This material was mutagenic in the Ames bacterial assay.

Mixture of triarylsulfonium/hexafluoroantimonate salts (CAS 71449-78-0 and 89452-37-9) in propylene carbonate (CAS 108-32-7):

This material was mutagenic in the Ames bacterial assay. It is inactive, however, in the in vivo mouse micronucleus test.

Propylene carbonate (CAS 108-32-7):

This substance had a negative Ames test with or without metabolic activation.

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (CAS 2530-83-8):

This material was weakly mutagenic in the Ames test, mouse lymphoma assay, and an in vitro sister chromatid exchange test; however results of in vivo genotoxicity studies have shown mixed results. Repeated exposure of rats or rabbits to this material did not result in an increase in sister chromatid exchange, while single exposures of mice to a hydrosylate of this materials resulted in a significant increase in micronucleated polychromatic erythrocytes. The potential releavance to humans is unknown; however, it is ulikely that this material presents a significant genotoxic hazard, in that it lacks any local tumorigneic response the the chronic recurrent application to mouse skin.

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Experience with humans: No further relevant information available.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· NTP (National Toxicology Program)

None of the ingredients are listed.

12 Ecological information

· Toxicity

| · Aquatic toxicity: | |
|-----------------------------------------------------------|-----------------|
| 89452-37-9 Bis-triarylsulfonium hexafluoroantimonate salt | |
| EC50/17 h >10000 mg/l (Pseudomonas putida) | |
| EC50/48 h >500 mg/l (daphnia magna) | |
| EC50/72 h >500 mg/l (scenedesmus subspicatus) | |
| 71449-78-0 Aromatic sulfonium hexafluoroantimonate salt | |
| EC50/17 h >10000 mg/l (Pseudomonas putida) | |
| EC50/48 h >500 mg/l (daphnia magna) | |
| EC50/72 h >500 mg/l (scenedesmus subspicatus) | |
| <u> </u> | (Contd. on page |

ntd. on page 9



Printing date 09/03/2013 Reviewed on 07/16/2013

Trade name: SU-8 3000 Series Resists

(Contd. of page 8)

120-92-3 Cyclopentanone

EC50/48 h | 100 mg/l (daphnia magna)

EC50/72 h >100 mg/l (scenedesmus subspicatus)

|LC50/96 h| > 100 mg/l (fish)|

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Disposal must be made in accordance with Federal, State, and Local regulations.

Must not be disposed of as regular garbage/trash. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made in accordance with Federal, State, and Local regulations.

14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA UN1866
- · UN proper shipping name
- · DOT, IMDG, IATA

RESIN SOLUTION

1866 RESIN SOLUTION

- · Transport hazard class(es)
- $\cdot DOT$

 $\cdot ADR$



· Class 3 Flammable liquids.

(Contd. on page 10)



Printing date 09/03/2013 Reviewed on 07/16/2013

Trade name: SU-8 3000 Series Resists

(Contd. of page 9) · Label · ADR, IMDG, IATA · Class 3 Flammable liquids · Label · Packing group · DOT, ADR, IMDG, IATA III· Environmental hazards: · Marine pollutant: No· Special precautions for user Warning: Flammable liquids · Danger code (Kemler): · EMS Number: F-E,S-E· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · UN "Model Regulation": UN1866, RESIN SOLUTION, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

| · Section 355 | (extremely l | hazardous | substances) | : |
|---------------|--------------|-----------|-------------|---|
|---------------|--------------|-----------|-------------|---|

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

89452-37-9 Bis-triarylsulfonium hexafluoroantimonate salt

71449-78-0 Aromatic sulfonium hexafluoroantimonate salt

· TSCA (Toxic Substances Control Act):

All ingredients are listed or comply with TSCA regulations.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

(Contd. on page 11)

Printing date 09/03/2013 Reviewed on 07/16/2013

Trade name: SU-8 3000 Series Resists

(Contd. of page 10)

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

· Massachusetts State Right To Know List

120-92-3 Cyclopentanone

· New Jersey State Right To Know List

120-92-3 Cyclopentanone

· Pennsylvania Hazardous Substances List

120-92-3 Cyclopentanone

- · California SCAQMD Rule 443.1 VOC's: See Table 1 Section 9
- · GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS07

GHS08 GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

Cyclopentanone

Epoxy resin

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Formaldehyde Polymer

Bis-triarylsulfonium hexafluoroantimonate salt

Aromatic sulfonium hexafluoroantimonate salt

· Hazard statements

H226 Flammable liquid and vapor.

H302+H312 Harmful if swallowed or in contact with skin.

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P233 Keep container tightly closed.
 P273 Avoid release to the environment.
 P201 Obtain special instructions before use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention.

(Contd. on page 12)



Printing date 09/03/2013 Reviewed on 07/16/2013

Trade name: SU-8 3000 Series Resists

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P327 P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use for extinction: Alcohol resistant foam.
P370+P378 In case of fire: Use for extinction: Fire-extinguishing powder.

P370+P378 In case of fire: Use for extinction: Carbon dioxide.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Product safety department

· Contact: Mr. Weber

· Last Revision Date:

7/16/2013 Revised hazard classification and precautionary statements. Updated component toxicology data.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

-USA